

# **BASI** BT 155 At €2-22






The BT 75 ATEX models are industrial vacuum cleaners of the DASIG line with pocket or stellar filters.

They can be powered with single-phase or three-phase turbine. The vertical design allows the employment even in the tightest spaces of every application sector for general suction of dust, and their reliability is guaranteed by the motor with side channel turbine which allows continuous use.

### WORK EFFICIENCY



USEFUL RATING FOR THE COMPARISON WITH OTHER MODELS FROM OUR RANGE

TYPE OF APPLICATION

DEGREE OF SPECIFICITY ( ) ( ) ( ) ( )

# TECHNICAL DATAS

TEOTIMONE BATTAC						
PASIG	BT 751 M-ANT At <mark>∰ 2-22</mark>	BT 751 M-ANT - EKU At <mark>∰ 2-22</mark>	BT 753 M-ANT At <b>∰ 2-22</b>	BT 753 M-ANT - EKU At <mark>∰ 2-22</mark>		
MOTORIZATION	TURBINE	TURBINE	TURBINE	TURBINE		
POWER	2,2 kW	2,2 kW	3 kW	3 kW		
VOLTAGE	230 V 😯	230 V 😯	400 V 🐼	400 V 🚱		
FREQUENCY	50 Hz	50 Hz	50-60 Hz	50-60 Hz		
AIR FLOW	320 m3/h	320 m3/h	320 m3/h	320 m3/h		
MAX DEPRESSION	300 mBar	300 mBar	320 mBar	320 mBar		
VACUUM VALVE	200 mBar	200 mBar	250 mBar	250 mBar		
CAPACITY	75 L	75 L	75 L	75 L		
DIMENSIONS	80x60 h154 cm	80x60 h154 cm	80x60 h154 cm	80x60 h154 cm		
WEIGHT	100 Kg	100 Kg	100 Kg	100 Kg		
FILTER SHAKER	MANUAL	MANUAL	MANUAL	MANUAL		
FILTER TYPE	POCKET	POCKET	POCKET	POCKET		
SURFACE	20000 CM <sup>2</sup>	20000 CM <sup>2</sup>	20000 CM <sup>2</sup>	20000 CM <sup>2</sup>		
FILTRATION/PROPERTIES	M - ANTISTATIC	M - ANTISTATICO FLAMEPROOF	M - ANTISTATIC	M - ANTISTATICO FLAMEPROOF		






BT 155 ATEX is the vacuum cleaner that combines power and reliability.

Designed and built for constant and continuous use is critical for companies that need a good suction power for vacuuming non-specific dust or debris that can be fine dust.

### WORK EFFICIENCY



USEFUL RATING FOR THE COMPARISON WITH OTHER MODELS FROM OUR RANGE

TYPE OF APPLICATION

DUST

DEGREE OF SPECIFICITY





# TECHNICAL DATAS

EASIS	BTP 155 m-ant At <mark>₩ 2-22</mark>	BTP 155 M-ANT - EKU At <mark>{ 2-22</mark>	BTS 155 M-ANT At <mark>{}} 2-22</mark>	BTS 155 M-ANT - EKU At <mark>{}} 2-22</mark>
MOTORIZATION	TURBINE	TURBINE	TURBINE	TURBINE
POWER	5,2 kW	5,2 kW	5,2 kW	5,2 kW
VOLTAGE	400 V 😵	400 V 😯	400 V 🚱	400 V 😥
FREQUENCY	50-60 Hz	50-60 Hz	50-60 Hz	50-60 Hz
AIR FLOW	520 m3/h	520 m3/h	320 m3/h	320 m3/h
MAX DEPRESSION	320 mBar	320 mBar	530 mBar	530 mBar
VACUUM VALVE	240 mBar	240 mBar	400 mBar	400 mBar
CAPACITY	100 L	100 L	100 L	100 L
DIMENSIONS	100x60 h140 cm	100x60 h140 cm	100x60 h140 cm	100x60 h140 cm
WEIGHT	150 Kg	150 Kg	150 Kg	150 Kg
FILTER SHAKER	MANUAL	MANUAL	MANUAL	MANUAL
FILTER TYPE	POCKET	POCKET	POCKET	POCKET
SURFACE	20000 CM <sup>2</sup>	20000 CM <sup>2</sup>	20000 CM <sup>2</sup>	20000 CM <sup>2</sup>
FILTRATION/PROPERTIES	M - ANTISTATIC	M - ANTISTATICO FLAMEPROOF	M - ANTISTATIC	M - ANTISTATICO FLAMEPROOF